



Precision Parts Co., Ltd.



E-TU-TRB-35MM Bearing 2D drawings and 3D CAD models

TIMKEN E-TU-TRB-35MM Take Up Unit Bearings

Bearing No. E-TU-TRB-35MM

Category	Take Up Unit Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	3.63
EAN	0053893550107
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row Double Collar Wide Slot Two Lip Seal Electrodeposition Coating With Set Screw
Inch - Metric	Metric
Long Description	Take Up Bearing Only; 35MM Bore; 13.5MM Slot Width; 89MM Slot to Slot Distance; Tapered Roller Bearing; Unit Only; Concentric Collar Mount; Cast Iron Housing Material
Category	Take Up Units
UNSPSC	31171533



Precision Parts Co., Ltd.

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Take Up
Manufacturer URL	http://www.timken.com
Weight / LBS	8
Slot Width	0.531 Inch 13.5 Millimeter
d	1.378 Inch 35 Millimeter
Slot to Slot Distance	3.504 Inch 89 Millimeter
Shaft Size	1.378 in
Shaft Size Type	Metric
Weight	8.00 lb
UPC Code	053893550107
Dimension B	3 in
Dimension L	5-3/32 in
Dimension A ₁	17/32 in
Dimension L ₃	2-3/4 in
Dimension L ₁	3-7/32 in
Dimension N	7/8 in
Dimension L ₂	11/16 in
Dimension N ₁	5/8 in
Dimension H ₂	2-7/16 in
Dimension N ₂	1-7/16 in
Dimension d ₁	2-3/4 in
Dimension H ₁	3-1/2 in
Dimension H	4-1/8 in
Dimension A ₂	2-1/16 in
e	0.46
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	1.89
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.28
K Factor	1.31



Precision Parts Co., Ltd.

C_{90} Dynamic Load Rating ¹	6100 lb
C_0 Static Load Rating	26000 lb
F_{a-max} Maximum Permissible Thrust Load ²	2590 lb
F_{r-max} Maximum Allowable Slip Fit Radial Load ³	5000 lb
Max. Speed ⁴	3820 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur