



Precision Parts Co., Ltd.



VAK 15/16 Bearing 2D drawings and 3D CAD models

0.938 Inch | 23.825 Millimeter x 1.219 Inch |
30.963 Millimeter x 1.313 Inch | 33.35 Millimeter
TIMKEN VAK 15/16 Pillow Block Bearings

Bearing No. VAK 15/16

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.76
EAN	0087796057081
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	GRA015RRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Spherical Normal Duty Low Base With Set Screw
Long Description	2 Bolt Pillow Block; 15/16" Bore; 1-5/16" Base to Center Height; Eccentric Collar



Precision Parts Co., Ltd.

	Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	VAK 15/16
Weight / LBS	1.67
d	0.938 Inch 23.825 Millimeter
Actual Bolt Center to Center	4.1 Inch 105Millimeter
B	1.313 Inch 33.35 Millimeter
D	1.219 Inch 30.963 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Nominal Bolt Center to Center	4.1 Inch 105 Millimeter
Shaft Size d	15/16 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.705 in
Series	Standard
Weight	1.671 lb
Seal Type	Molded Shroud
Base to Center Height H	33.34 mm
Total Length L	139.70 mm



Precision Parts Co., Ltd.

Total Width A	1.406 in
Bolt Hole Spacing J	104.8 mm
Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	20.6 mm
Foot Height H1	11.9 mm
Total Height H2	68.3 mm
Dimension L1	46.6 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	7.6 mm
Dimension B1	1.220 in
Static Load Rating	1750 lbf
Dynamic Load Rating	3490 lbf